

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	0250A1NL		
	Product Name:	CARBOZINC 11 / CARBOZINC 11 FG BASE	Revision Date:	04/09/2019
1.2	Relevant identified uses of the substance or mixture and uses advised against	Base component of 2 components coatings - Industrial use.	Supercedes Date:	10/09/2018
1.3	Details of the supplier of the safety data sheet			
	Manufacturer:	Carboline Company 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Information: Contact Carboline Technical Services at 1-800-848-4645		
	Datasheet Produced by:	Alotta, Vicki - ehs@stoncor.com		
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Insi CHEMTREC +1 703 5273887 (Out HEALTH - Pittsburgh Poison Contr	tside ÚS)	

# 2. Hazard Identification

# 2.1 Classification of the substance or mixture

Acute Toxicity, Dermal, category 4 Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A Eye Irritation, category 2 Flammable Liquid, category 2 STOT, repeated exposure, category 1 Skin Irritation, category 2

# 2.2 Label elements

# Symbol(s) of Product



Signal Word

Danger

## Named Chemicals on Label

METHYL ALCOHOL, ETHYL SILICATE, ETHYL BENZENE, 2-BUTOXYETHANOL, MICROCRYSTALLINE SILICA

## HAZARD STATEMENTS

Flammable Liquid, category 2 Acute Toxicity, Dermal, category 4 Skin Irritation, category 2 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A STOT, repeated exposure, category 1	H225 H312 H315 H319 H332 H350-1A H372	Highly flammable liquid and vapour. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
PRECAUTION PHRASES		
	P201 P202	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P235	Keep cool.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P302	IF ON SKIN:
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P314	Get medical advice/attention if you feel unwell.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P352	Wash with plenty of soap and water.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.

# 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment: Unknown

Product: 0250A1NL

# 3. Composition/Information On Ingredients

## 3.2 Mixtures

## Hazardous Ingredients

<u>CAS-No.</u> 64-17-5 14808-60-7 67-63-0 111-76-2 67-56-1 78-10-4 13463-67-7 12001-26-2 1333-86-4 100-41-4	Chemical Name ETHYL ALCOHOL MICROCRYSTALLINE SILICA ISOPROPANOL 2-BUTOXYETHANOL METHYL ALCOHOL ETHYL SILICATE TITANIUM DIOXIDE MICA CARBON BLACK ETHYL BENZENE		$\begin{array}{c} \label{eq:25} \begin{tabular}{lllllllllllllllllllllllllllllllllll$
CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
64-17-5	GHS02	H225	0
14808-60-7	GHS08	H350-372	0
67-63-0	GHS02-GHS07	H225-319-336	0
111-76-2	GHS07	H302-312-315-319-332	0
67-56-1	GHS02-GHS06-GHS08	H225-301-311-331-370	0
78-10-4	GHS02-GHS07	H226-319-332-335	0
13463-67-7			0
12001-26-2	GHS07	H319-335	0
1333-86-4			0
100-41-4	GHS02-GHS07-GHS08	H225-304-315-319-332-351-373-412	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

# 4. First-aid Measures

## 4.1 Description of First Aid Measures

**AFTER INHALATION:** Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

**AFTER SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness.

## 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

# 5. Fire-fighting Measures

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety

standards. Wear shoes with conductive soles.

5.2 Special hazards arising from the substance or mixture No Information

## 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

# 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

## 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

# 7. Handling and Storage

## 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING :** Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

**PROTECTION AND HYGIENE MEASURES :** Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### CONDITIONS TO AVOID: Heat, flames and sparks.

**STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

No specific advice for end use available.

# 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
ETHYL ALCOHOL	64-17-5	N/E	1000 PPM	N/E
MICROCRYSTALLINE SILICA	14808-60-7	0.025 MGM3	N/E	N/E
ISOPROPANOL	67-63-0	200 PPM	400 PPM	N/E

Date Printed: 04/09/2019

N/E N/E N/E N/E N/E

2	-BUTOXYETHANOL	111-76-2	20 PPM	50 PPM	ļ
Ν	IETHYL ALCOHOL	67-56-1	200 PPM	250 PPM	ļ
Е	THYL SILICATE	78-10-4	10 PPM	N/E	ļ
Т	TTANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	ļ
Ν	/ICA	12001-26-2	3 MGM3	N/E	ļ
С	CARBON BLACK	1333-86-4	3 MGM3	N/E	ļ
E	THYL BENZENE	100-41-4	20 PPM	125 ppm	
N	<u>lame</u>	CAS-No.	<u>OSHA PEL</u>	OSHA STEL	
E	ETHYL ALCOHOL	64-17-5	1900 MGM3, 1000 PPM	N/E	
N	/ICROCRYSTALLINE SILICA	14808-60-7	0.05 MGM3	N/E	
1	SOPROPANOL	67-63-0	980 MGM3, 400 PPM	1225 MGM3, 500 PPM	
2	2-BUTOXYETHANOL	111-76-2	120 MGM3, 25 PPM	N/E	
N	IETHYL ALCOHOL	67-56-1	260 MGM3, 2003 PPM	325 MGM3, 250 PPM	
E	ETHYL SILICATE	78-10-4	85 MGM3, 10 PPM	N/E	
T	TTANIUM DIOXIDE	13463-67-7	15 MGM3	N/E	
N	ЛICA	12001-26-2	20. MPPCF	N/E	
C	CARBON BLACK	1333-86-4	3.5 MG/M3	N/E	
E	THYL BENZENE	100-41-4	435 MGM3, 1005 PPM	545 MGM3, 125 PPM	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

## 8.2 Exposure controls

## Personal Protection

**RESPIRATORY PROTECTION:** In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses with side-shields.

**HAND PROTECTION:** Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

# 9.1 Information on basic physical and chemical properties

Appearance:	Viscous Green, Grey, Red Or
Physical State	Liquid
Odor	Solvent
Odor threshold	N/D
рН	N/D
Melting point / freezing point (°C)	N/D
Boiling point/range	149 F (65 C) - 340 F (171 C)
Flash Point	56F (13C)
Evaporation rate	Slower Than Ether
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	1.0 - 36.0
Vapour Pressure, mmHg	N/D
Vapour density	Heavier than Air
Relative density	Not determined
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Unknown
Explosive properties	Not determined
Oxidising properties	Not determined
Other information	
VOC Content g/l:	C741- 470- C744 FC- 545
-	CZ11: 479; CZ11 FG: 515
Specific Gravity (g/cm3)	1.07

# 10. Stability and Reactivity

## 10.1 Reactivity

9.2

No reactivity hazards known under normal storage and use conditions.

# 10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions Hazardous polymerisation does not occur.

# 10.4 Conditions to avoid

Heat, flames and sparks.

## 10.5 Incompatible materials Strong oxidizing agents.

# 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

	=		
11.1	Information on toxicological effects		
	Acute Toxicity:		
	Oral LD50:	N/D	
	Inhalation LC50:	N/D	
	Irritation:	Eye Irritation and Skin Irritation, category 2	
	Corrosivity:	Unknown	
	Sensitization:	Unknown	
	Repeated dose toxicity:	STOT, repeated exposure, category 1	
	Carcinogenicity:	Carcinogenicity, category 1A	
	Mutagenicity:	Unknown	
	Toxicity for reproduction:	Unknown	
	STOT-single exposure:	Unknown	
	STOT-repeated exposure:	Unknown	
	Aspiration hazard:	Unknown	

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
64-17-5	ETHYL ALCOHOL	7060 mg/kg, oral, rat		20000 ppm/10 hrs, rat, inhalation	0.000	0.000
14808-60-7	MICROCRYSTALLINE SILICA	22500 mg/kg	Not Available	Not Available	0.000	0.000
67-63-0	ISOPROPANOL	4720 mg/kg rat, oral	12800 mg/kg, dermal, rabbit	22500 ppm/8hrs rat, inhalation	0.000	0.000
111-76-2	2-BUTOXYETHANOL	1300 mg/kg, oral, rat	2000 mg/kg, dermal, rat	450 ppm/l / 4H, rat, Inhalation	0.000	0.000
67-56-1	METHYL ALCOHOL	2080 mg/kg rat oral	Not Available	Not Available	0.000	0.000
78-10-4	ETHYL SILICATE	>2000mg/kg rat, oral		>7.5 mg/L 4 hrs. rat, inhalation	0.000	0.000
13463-67-7	TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information
12001-26-2	MICA	Not Available	Not Available	Not Available	0.000	0.000
1333-86-4	CARBON BLACK	8000 mg/kg oral, rat	Not Available	Not Available		

100-41-4	ETHYL BENZENE	3500 mg/kg rat, oral	>5000 mg/l, dermal rabbit	17.2 mg/L Inh, Rat, 4Hr	0.000	0.000
----------	---------------	-------------------------	------------------------------	----------------------------	-------	-------

## Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This product contains silica which is classified by IARC as a known human carcinogen (Group 1). Crystalline silica is known to cause silicosis. The classification(s) is/are relevant when exposed to these respirable substances in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

# 12. Ecological Information

12.1 Toxicity:

	EC50 48hr (Daphnia):	Unknown
	IC50 72hr (Algae):	Unknown
	LC50 96hr (fish):	Unknown
12.2	Persistence and degradability:	Unknown
12.3	Bioaccumulative potential:	Unknown
12.4	Mobility in soil:	Unknown
12.5	Results of PBT and vPvB assessment:	Unknown

12.6 Other adverse effects:

Unknown

CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
64-17-5	ETHYL ALCOHOL	2 mg/l (Daphnia Magna)	No information	42 mg/l (fish)
14808-60-7	MICROCRYSTALLINE SILICA	No information	No information	No information
67-63-0	ISOPROPANOL	13299 mg/l (Daphnia Magna)	>1000 m/gL (desmodesmus subspicatus)	9640 mg/L (pimphales promelas)
111-76-2	2-BUTOXYETHANOL	1800 mg/l (Water flea)	911 mg/l (Algae)	1474 mg/kg (Fish)
67-56-1	METHYL ALCOHOL	No information	No information	No information
78-10-4	ETHYL SILICATE	No information	No information	No information
13463-67-7	TITANIUM DIOXIDE	No information	No information	No information
12001-26-2	MICA	No information	No information	No information
1333-86-4	CARBON BLACK	No information	No information	No information
100-41-4	ETHYL BENZENE	1.8 mg/l (Daphnia Magna)	4.6 mg/l (Green Algae)	4.2 mg/l (Rainbow Trout)

# 13. Disposal Considerations

**13.1** WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

17.		
14.1	UN number	UN 1263
14.2	UN proper shipping name	Paint
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	II
14.5	Environmental hazards	Unknown
14.6	Special precautions for user	Unknown
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

# **15. Regulatory Information**

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

## Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
ISOPROPANOL	67-63-0
METHYL ALCOHOL	67-56-1
ETHYL BENZENE	100-41-4

#### **Toxic Substances Control Act:**

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

## Chemical Name

No TSCA 12(b) components exist in this product.

## U.S. State Regulations: As follows -

## New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

## Chemical Name

No NJ Right-To-Know components exist in this product.

# Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

## **Chemical Name**

CAS-No.

CAS-No.

CAS-No.

ALUMINUM SILICATE	1332-58-7
WATER	7732-18-5

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

# International Regulations: As follows -

## \* Canadian DSL:

All chemical ingredients included on inventory (DSL)

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour.	
H301 Toxic if swallowed.	
H302 Harmful if swallowed.	
H304 May be fatal if swallowed and enters airways.	
H311 Toxic in contact with skin.	
H312 Harmful in contact with skin.	
H315 Causes skin irritation.	
H319 Causes serious eye irritation.	
H331 Toxic if inhaled.	
H332 Harmful if inhaled.	
H335 May cause respiratory irritation.	
H336 May cause drowsiness or dizziness.	
H350 May cause cancer.	
H351 Suspected of causing cancer.	
H370 Causes damage to organs.	
H372 Causes damage to organs through prolonged or repeated exposure.	
H373 May cause damage to organs through prolonged or repeated exposu	re.
H412 Harmful to aquatic life with long lasting effects.	

## Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.